

EXTERIOR HIGH BUILD WOOD OIL

A blend of natural oils and resins offering a transparent satin finish with exceptional durability and resistance for all external timber and joinery. Produces a clear, quick drying, water repellent and weather resistant finish that will not peel or flake when applied. Contains UV filters and is VOC compliant.

Preparation

- Ensure all surfaces are clean, dry and free from any previous finish.
- Remove any fungal growth, dirt or moss on old timber prior to application and ensure a preservative has been applied
- Sand the substrate with a medium 120 grade sanding paper or 120 grade sanding disk removing all traces of dust.

Application

- Apply in dry conditions and always test on a small area prior to initial application.
- No primer required
- Minimum 3 coats recommended
- Formulated for direct application and does not require thinning
- Stir contents thoroughly before and during use
- Apply using a good quality bristly or synthetic brush and apply evenly and thoroughly following the direction of the grain
- Leave to dry 4-6 hours or overnight with good ventilation
- Sand lightly with fine 320 grade sandpaper if required

Re-Application

- To renovate previous application, lightly sand area with 150 grade sandpaper and reapply
- Refresh annually

Coverage

Approximately 20sqm per litre depending on substrate

For all product enquiries and information please contact us today!

10/100 New Street, Ringwood, VIC 3134

Phone: (03) 8813 0338

Email: enquiries@fiddesaustralia.com

www.fiddesaustralia.com

