AUIN00681 Intergrain Floor Cleaner

Introduction

Line Shade
701W0616

Description and Image

Intergrain Floor Cleaner is a concentrated water based cleaner designed for coated interior timber floors, stairs, parquetry and cork.



Features and Benefits

- Multi-purpose floor cleaner
- Removes scuff marks when used undiluted
- Streak-free finish
- Suitable for use in commercial cleaning machines and auto scrubbers

Uses

Use on coated interior timber floors, stairs, parquetry and cork.
Can also be used on prefinished floating floors and other coated surfaces such as vinyl, tiles and sealed concrete.

Precautions and Limitations

DO NOT use hot water.
Do not flood the floor with water or mixed cleaning solution.

Typical Properties

Clean Up

Water

Clean Up Description
Clean equipment and tools with water

Application Guide

Application Procedure and Equipment

Dust mop the floor to remove any loose dirt, dust or grit.

Manual cleaning
Add approximately 50ml Intergrain Floor Cleaner concentrate (2 capfuls) to 4L of cold or lukewarm water. DO NOT use hot water. Apply solution with a damp mop and allow to dry.

Commercial cleaning machines or auto scrubbers
For general cleaning, suggested dilution ratio of 1:100. That is dilute 1 part Intergrain Floor Cleaner with 100 parts water, or 100ml Intergrain Floor Cleaner added to 10L of water.
For very dirty floors, use a stronger dilution. For example 1:40. That is dilute 1 part Intergrain Floor Cleaner into 40 parts water, or 100ml Intergrain Floor Cleaner added to 4L of water.
Use appropriate pad for the job, depending on condition of the floor, amount of soiling, and whether it is a routine maintenance clean or cleaning prior to recoat.

Intergrain Floor Cleaner can also be used undiluted to assists in the removal of black heal marks or stubborn stains.
Do not flood the floor.
Intergrain Floor Cleaner should not be used on fresh coatings that are less than 2 weeks old.

*When used undiluted

Health and Safety

SDS Number	SDS Link
DLXGHSEN005094	

Using Safety Precautions
Refer to SDS

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

Intergrain Floor Cleaner

Size:	Weight:
1L 4L	1.10kg 4.20kg

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.