



Toby GF Barrier Seal

AUDW1208

Part A	70372030
--------	----------



Description
TOBY GF BARRIER SEAL is a fast drying (1.5 hour recoat time) sealer for timber and parquetry floors. It offers outstanding barrier properties. The product can reduce the occurrence of rejection and tannin bleed on oily and tannin rich timbers. It also has good colour development.

Features
<ul style="list-style-type: none"> • Easy application • Excellent adhesion properties • Excellent barrier properties

Uses
Timber and parquetry floors

Precautions And Limitations
Do not apply product if temperature is below 10°C or above 35°C. Relative humidity should not exceed 85%.

Performance Guide	
Weather	Interior Only

Typical Properties																											
Colour	Clear	Components	1																								
Number Of Coats	1	V.O.C. Level	< 715g/L																								
Touch Dry	30 minutes																										
Clean Up Description	Feast Watson Super Solvent. To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.																										
Application Method	 Brush  Roller																										
Application Conditions	<table border="1"> <tr> <td>Solids By Volume</td> <td>12</td> <td></td> <td></td> </tr> <tr> <td></td> <td>Min</td> <td>Max</td> <td>Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td>80</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td>13</td> </tr> <tr> <td>Recoat Time (min)</td> <td>1.5 hours</td> <td></td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td></td> <td>12</td> <td>12</td> </tr> </table>	Solids By Volume	12				Min	Max	Recommended	Wet Film Per Coat (microns)			80	Dry Film Per Coat (microns)			13	Recoat Time (min)	1.5 hours			Theoretical Spread Rate (m ² /L)		12	12		
Solids By Volume	12																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			80																								
Dry Film Per Coat (microns)			13																								
Recoat Time (min)	1.5 hours																										
Theoretical Spread Rate (m ² /L)		12	12																								
Typical Properties Notes	COVERAGE 10-12 square metres per litre depending on the porosity of the timber. DRY TIMES Touch Dry: 30 minutes Recoat: 1.5 hours These dry times are based on drying conditions of 25°C and 50% relative humidity. Dry times will be subject to climatic conditions, film thickness and airflow.																										



Application Guide

<p>Surface Preparation</p>	<ul style="list-style-type: none"> All surfaces must be clean, dry, free of wax, grease, dust and other contaminants. The presence of contaminants contributes to conditions such as 'rejection' or 'delamination'. If uneven, the surface should be sanded with coarse sandpaper. All nail-holes and cracks should be filled with a water based putty. Do not use linseed oil putty. Fine sand the floor, finishing with 100-grit sandpaper, then with 120-mesh screenback (when using a solvent based top coat) or 150-mesh screen back (when using a water based top coat) and vacuum thoroughly with a commercial grade vacuum cleaner. If the surface has been previously coated ensure that it is thoroughly sanded to remove old coating.
<p>Application Procedure And Equipment</p>	<ul style="list-style-type: none"> Apply one coat of TOBY GF BARRIER SEAL by brush or with a 6mm mohair roller. If sanding of the sealer is required use a worn 150 mesh screen. <p>Finishing Apply two coats of the TOBY solvent or water based finish as per instructions.</p>



Health And Safety			
MSDS Number	DLXGHCEN003247	Using Safety Precautions	<p>Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness. Keep out of reach of children. Read the label before opening or using. Keep away from all sources of ignition – No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Do not eat, drink or smoke when using this product. Avoid breathing mist, vapours or spray. Wear protective clothing, gloves, eye/face protection and a suitable respirator as required. Wash contaminated clothing before reuse. Wash hands, face and all exposed skin thoroughly after handling. Keep container tightly closed. Store locked up. Store in a well ventilated place, away from foodstuffs and oxidising agents. Keep cool. Do not empty into drains.</p> <p>FOR SPILLS: Clear area of all unprotected personnel. Slippery when spilt. Wear protective equipment. Absorb with sand or soil. Collect and seal in properly labelled drums. Dispose of contents/container in accordance with local, regional, national and international regulations.</p>
Health Effects	<p>FIRST AID: If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766). If medical advice is needed, have product container or label at hand.</p> <p>SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.</p> <p>EYE: If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.</p> <p>SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If irritation occurs seek medical advice.</p> <p>INHALED: Remove from contaminated area. Apply artificial respiration if not breathing. Seek medical advice.</p>	Flammability	This product is highly flammable.
Fire Suppression	If involved in a fire use alcohol resistant foam. If unavailable, use standard foam or dry agents. Avoid breathing products of combustion.	Protective Equipment	Wear protective clothing, gloves, eye/face protection and a suitable respirator as required.
Storage	Keep out of reach of children. Protect from extremes of temperature. Store between 5°C and 30°C.	Disposal	Do not pour leftover product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty product containers via domestic recycling programs may differ between local authorities. Check with your local council first.
Other	CONTAINS: 30-60% ETHANOL, 10-30% N-BUTYL ACETATE, 10-30% N-BUTYL ALCOHOL		
In the case of emergency, please call 1800 033 111			



Transport And Storage			
Pack A	70372030	Shipment Name	PAINT
Size 20Kg	Weight 19.7Kg		
Flash Point	13C	UN Number	1263
Dangerous Goods Class	3	Package Group	I

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.
 DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427