

Urethane Coatings a division of Era Polymers Pty Ltd

Chemwatch Hazard Alert Code: 2

Catalogue number: **UC TUNGSEAL - AUSTRALIA**
Version No: **1.1**
Safety Data Sheet according to WHS and ADG requirements

Issue Date: **08/12/2016**
Print Date: **08/12/2016**
S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

| | |
|--------------------------------------|--|
| Product name | TUNGSEAL |
| Synonyms | Not Available |
| Proper shipping name | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| Other means of identification | Not Available |

Relevant identified uses of the substance or mixture and uses advised against

| | |
|---------------------------------|--|
| Relevant identified uses | Sealer and finish for timber, parquetry, or cork flooring. |
|---------------------------------|--|

Details of the supplier of the safety data sheet

| | |
|--------------------------------|--|
| Registered company name | Urethane Coatings a division of Era Polymers Pty Ltd |
| Address | 2-4 Green Street, Banksmeadow NSW 2019 Australia |
| Telephone | +61 (0)2 9666 3888 |
| Fax | +61 (0)2 9666 4805 |
| Website | www.urethanecoatings.com.au |
| Email | george@urethanecoatings.com.au |

Emergency telephone number

| | |
|--|----------------|
| Association / Organisation | CHEMWATCH |
| Emergency telephone numbers | 1800 039 008 |
| Other emergency telephone numbers | +612 9186 1132 |

CHEMWATCH EMERGENCY RESPONSE

| Primary Number | Alternative Number 1 | Alternative Number 2 |
|----------------|----------------------|----------------------|
| 1800 039 008 | 1800 039 008 | +612 9186 1132 |

Once connected and if the message is not in your preferred language then please dial 01


SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

| | |
|---------------------------|--|
| Poisons Schedule | S5 |
| Classification [1] | Aspiration Hazard Category 1, Specific target organ toxicity - repeated exposure Category 1, Flammable Liquid Category 3 |
| Legend: | 1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI |

Label elements

| | |
|---------------------------|---|
| GHS label elements |  |
| SIGNAL WORD | DANGER |

Hazard statement(s)

| | |
|--------|---|
| H304 | May be fatal if swallowed and enters airways. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| AUH066 | Repeated exposure may cause skin dryness and cracking |
| H226 | Flammable liquid and vapour. |

Precautionary statement(s) Prevention

| | |
|------|---|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P103 | Read label before use. |
| P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. |
| P233 | Keep container tightly closed. |

Precautionary statement(s) Response

| | |
|----------------|--|
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. |
| P331 | Do NOT induce vomiting. |
| P370+P378 | In case of fire: Use alcohol resistant foam or normal protein foam for extinction. |
| P314 | Get medical advice/attention if you feel unwell. |
| P303+P361+P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. |

Precautionary statement(s) Storage

| | |
|-----------|--|
| P403+P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |

Precautionary statement(s) Disposal

| | |
|------|---|
| P501 | Dispose of contents/container in accordance with local regulations. |
|------|---|

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**Substances**

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name |
|---------------|-----------|--|
| 64742-82-1. | 10-30 | <u>naphtha, petroleum, hydrodesulfurised heavy</u> |
| 1330-20-7 | 1-10 | <u>xylene</u> |
| 872-50-4 | <1 | <u>N-methyl-2-pyrrolidone</u> |
| Not Available | to 100 | All other substances non hazardous |

SECTION 4 FIRST AID MEASURES**Description of first aid measures**

| | |
|---------------------|--|
| Eye Contact | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
| Skin Contact | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation. |
| Inhalation | <ul style="list-style-type: none"> ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary. |
| Ingestion | <ul style="list-style-type: none"> ▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus. ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Seek medical advice. ▶ Avoid giving milk or oils. ▶ Avoid giving alcohol. |

Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for

difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

For acute or short term repeated exposures to xylene:

- ▶ Gastro-intestinal absorption is significant with ingestions. For ingestions exceeding 1-2 ml (xylene)/kg, intubation and lavage with cuffed endotracheal tube is recommended. The use of charcoal and cathartics is equivocal.
- ▶ Pulmonary absorption is rapid with about 60-65% retained at rest.
- ▶ Primary threat to life from ingestion and/or inhalation, is respiratory failure.
- ▶ Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ < 50 mm Hg or pCO₂ > 50 mm Hg) should be intubated.
- ▶ Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- ▶ A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- ▶ Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

| Determinant | Index | Sampling Time | Comments |
|--------------------------------|----------------------------------|-------------------------------------|----------|
| Methylhippu-ric acids in urine | 1.5 gm/gm creatinine 2 mg/min | End of shift Last 4 hrs of shift | |

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

Special hazards arising from the substrate or mixture

| | |
|-----------------------------|--|
| Fire Incompatibility | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

Advice for firefighters

| | |
|------------------------------|---|
| Fire Fighting | <ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be violently or explosively reactive. ▶ Wear breathing apparatus plus protective gloves. ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ If safe, switch off electrical equipment until vapour fire hazard removed. |
| Fire/Explosion Hazard | <ul style="list-style-type: none"> ▶ Liquid and vapour are flammable. ▶ Moderate fire hazard when exposed to heat or flame. ▶ Vapour forms an explosive mixture with air. ▶ Moderate explosion hazard when exposed to heat or flame. ▶ Vapour may travel a considerable distance to source of ignition. Combustion products include: carbon monoxide (CO) carbon dioxide (CO ₂) other pyrolysis products typical of burning organic material. |
| HAZCHEM | •3Y |

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| | |
|---------------------|---|
| Minor Spills | <ul style="list-style-type: none"> ▶ Remove all ignition sources. ▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes. ▶ Control personal contact with the substance, by using protective equipment. ▶ Contain and absorb small quantities with vermiculite or other absorbent material. |
| Major Spills | <ul style="list-style-type: none"> ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be violently or explosively reactive. ▶ Wear breathing apparatus plus protective gloves. ▶ Prevent, by any means available, spillage from entering drains or water course. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

| | |
|----------------------|--|
| Safe handling | <ul style="list-style-type: none"> ▶ Containers, even those that have been emptied, may contain explosive vapours. ▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers. |
|----------------------|--|

| | |
|-------------------|--|
| | <ul style="list-style-type: none"> ▶ Electrostatic discharge may be generated during pumping - this may result in fire. ▶ Ensure electrical continuity by bonding and grounding (earthing) all equipment. ▶ Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ($\leq 1 \text{ m/sec} = \frac{\text{pipe diameter}}{7}$) ▶ Avoid splash filling. ▶ Do NOT use compressed air for filling discharging or handling operations. ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of overexposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps. ▶ DO NOT enter confined spaces until atmosphere has been checked. ▶ DO NOT allow clothing wet with material to stay in contact with skin |
| Other information | <ul style="list-style-type: none"> ▶ Store in original containers in approved flammable liquid storage area. ▶ Store away from incompatible materials in a cool, dry, well-ventilated area. ▶ DO NOT store in pits, depressions, basements or areas where vapours may be trapped. ▶ No smoking, naked lights, heat or ignition sources. ▶ Storage areas should be clearly identified, well illuminated, clear of obstruction and accessible only to trained and authorised personnel - adequate security must be provided so that unauthorised personnel do not have access. |

Conditions for safe storage, including any incompatibilities

| | |
|-------------------------|--|
| Suitable container | <ul style="list-style-type: none"> ▶ Packing as supplied by manufacturer. ▶ Plastic containers may only be used if approved for flammable liquid. ▶ Check that containers are clearly labelled and free from leaks. ▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure. ▶ For materials with a viscosity of at least 2680 cSt. (23 deg. C) ▶ For manufactured product having a viscosity of at least 250 cSt. (23 deg. C) ▶ Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used. |
| Storage incompatibility | <p>Xylenes:</p> <ul style="list-style-type: none"> ▶ may ignite or explode in contact with strong oxidisers, 1,3-dichloro-5,5-dimethylhydantoin, uranium fluoride ▶ attack some plastics, rubber and coatings ▶ may generate electrostatic charges on flow or agitation due to low conductivity. ▶ Vigorous reactions, sometimes amounting to explosions, can result from the contact between aromatic rings and strong oxidising agents. ▶ Aromatics can react exothermically with bases and with diazo compounds. |

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|------------------------------|---|----------------------------|--------------------|---------------------|---------------|---------------|
| Australia Exposure Standards | naphtha, petroleum, hydrodesulfurised heavy | White spirits | 790 mg/m3 | Not Available | Not Available | Not Available |
| Australia Exposure Standards | xylene | Xylene (o-, m-, p-isomers) | 350 mg/m3 / 80 ppm | 655 mg/m3 / 150 ppm | Not Available | Not Available |
| Australia Exposure Standards | N-methyl-2-pyrrolidone | 1-Methyl-2-pyrrolidone | 103 mg/m3 / 25 ppm | 309 mg/m3 / 75 ppm | Not Available | Sk |

EMERGENCY LIMITS

| Ingredient | Material name | TEEL-1 | TEEL-2 | TEEL-3 |
|---|--|---------------|---------------|---------------|
| naphtha, petroleum, hydrodesulfurised heavy | Naphtha, hydrotreated heavy; (Isopar L-rev 2) | 350 mg/m3 | 1,800 mg/m3 | 40,000 mg/m3 |
| naphtha, petroleum, hydrodesulfurised heavy | Petroleum distillates; petroleum ether; includes clay-treated light naphthenic [64742-45-6]; low boiling [68477-31-6]; petroleum extracts [64742-06-9]; petroleum base oil [64742-46-7]; petroleum 50 thinner, petroleum spirits [64475-85-0], Soltrol, VM&P naphtha [8032-32-4]; Ligroine, and paint solvent; petroleum paraffins C5-C20 [64771-72-8]; hydrotreated light naphthenic [64742-53-6]; solvent refined light naphthenic [64741-97-5]; and machine coolant 1 | 1,100 mg/m3 | 1,800 mg/m3 | 40,000 mg/m3 |
| naphtha, petroleum, hydrodesulfurised heavy | Naphtha (coal tar); includes solvent naphtha, petroleum (64742-88-7), naphtha (petroleum) light aliphatic, rubber solvent (64742-89-8), heavy catalytic cracked (64741-54-4), light straight run (64741-46-4), heavy aliphatic solvent (64742-96-7), high flash aromatic and aromatic solvent naphtha (64742-95-6) | 1,200 mg/m3 | 6,700 mg/m3 | 40,000 mg/m3 |
| naphtha, petroleum, hydrodesulfurised heavy | Stoddard solvent; (Mineral spirits, 85% nonane and 15% trimethyl benzene) | 300 mg/m3 | 1,800 mg/m3 | 29500 mg/m3 |
| xylene | Xylenes | Not Available | Not Available | Not Available |
| N-methyl-2-pyrrolidone | Methyl 2-pyrrolidinone, 1-; (N-Methylpyrrolidone) | 30 ppm | 32 ppm | 190 ppm |

| Ingredient | Original IDLH | Revised IDLH |
|---|--|--|
| naphtha, petroleum, hydrodesulfurised heavy | 29,500 mg/m3 / 10,000 ppm / 10,000 [LEL] ppm | 20,000 mg/m3 / 1,100 [LEL] ppm / 1,000 [LEL] ppm |
| xylene | 1,000 ppm | 900 ppm |
| N-methyl-2-pyrrolidone | Not Available | Not Available |
| All other substances non hazardous | Not Available | Not Available |

Exposure controls

| | |
|---|--|
| Appropriate engineering controls | Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. |
| Eye and face protection | <ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. |
| Skin protection | See Hand protection below |
| Hands/feet protection | <ul style="list-style-type: none"> ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. |
| Body protection | See Other protection below |
| Other protection | <ul style="list-style-type: none"> ▶ Overalls. ▶ PVC Apron. ▶ PVC protective suit may be required if exposure severe. ▶ Eyewash unit. ▶ Ensure there is ready access to a safety shower. • Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. • For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). • Non-sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot and shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. |
| Thermal hazards | Not Available |

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

'Forsberg Clothing Performance Index'.

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

TUNGSEAL

| Material | CPI |
|-------------------|-----|
| PE/EVAL/PE | A |
| PVA | B |
| BUTYL | C |
| BUTYL/NEOPRENE | C |
| HYPALON | C |
| NAT+NEOPR+NITRILE | C |
| NATURAL RUBBER | C |
| NATURAL+NEOPRENE | C |
| NEOPRENE | C |
| NEOPRENE/NATURAL | C |
| NITRILE | C |
| NITRILE+PVC | C |
| PVC | C |
| PVDC/PE/PVDC | C |
| TEFLON | C |
| VITON | C |

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as 'feel' or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

| Required minimum protection factor | Maximum gas/vapour concentration present in air p.p.m. (by volume) | Half-face Respirator | Full-Face Respirator |
|------------------------------------|--|----------------------|----------------------|
| up to 10 | 1000 | A-AUS / Class - 1 | |
| up to 50 | 1000 | - | A-AUS / Class 1 |
| up to 50 | 5000 | Airline * | - |
| up to 100 | 5000 | - | A-2 |
| up to 100 | 10000 | - | A-3 |
| 100+ | | - | Airline** |

* -Continuous Flow

** -Continuous-flow or positive pressure demand.

A (All classes) = Organic vapours, B AUS or B1 = Acid gases, B2 = Acid gas or hydrogen cyanide (HCN), B3 = Acid gas or hydrogen cyanide (HCN), E = Sulfur dioxide (SO₂), G = Agricultural chemicals, K = Ammonia (NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds (below 65 deg C)

Information on basic physical and chemical properties

| | | | |
|---|---------------------|--|---------------|
| Appearance | Clear yellow liquid | | |
| Physical state | Liquid | Relative density (Water = 1) | 0.89 |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available |
| pH (as supplied) | Not Available | Decomposition temperature | Not Available |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Available |
| Initial boiling point and boiling range (°C) | Not Available | Molecular weight (g/mol) | Not Available |
| Flash point (°C) | 37 | Taste | Not Available |
| Evaporation rate | Not Available | Explosive properties | Not Available |
| Flammability | Flammable. | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Available | Surface Tension (dyn/cm or mN/m) | Not Available |
| Lower Explosive Limit (%) | Not Available | Volatile Component (%vol) | Not Available |
| Vapour pressure (kPa) | Not Available | Gas group | Not Available |
| Solubility in water (g/L) | Immiscible | pH as a solution (1%) | Not Available |
| Vapour density (Air = 1) | Not Available | VOC g/L | Not Available |

SECTION 10 STABILITY AND REACTIVITY

| | |
|---|--|
| Reactivity | See section 7 |
| Chemical stability | <ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

| | | | |
|---------------------|---|----------|------------|
| Inhaled | <p>There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.</p> <p>The material has NOT been classified by EC Directives or other classification systems as 'harmful by inhalation'. This is because of the lack of corroborating animal or human evidence.</p> <p>Headache, fatigue, tiredness, irritability and digestive disturbances (nausea, loss of appetite and bloating) are the most common symptoms of xylene overexposure. Injury to the heart, liver, kidneys and nervous system has also been noted amongst workers.</p> <p>Xylene is a central nervous system depressant</p> | | |
| Ingestion | <p>Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)</p> <p>The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'. This is because of the lack of corroborating animal or human evidence.</p> | | |
| Skin Contact | <p>Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.</p> <p>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.</p> <p>There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p> | | |
| Eye | <p>There is some evidence to suggest that this material can cause eye irritation and damage in some persons.</p> | | |
| Chronic | <p>Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.</p> <p>This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.</p> <p>Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.</p> <p>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.</p> <p>There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.</p> <p>Women exposed to xylene in the first 3 months of pregnancy showed a slightly increased risk of miscarriage and birth defects. Evaluation of workers chronically exposed to xylene has demonstrated lack of genetic toxicity.</p> <p>Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS]</p> <p>Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin.</p> | | |
| TUNGSEAL | <table border="1"> <tr> <td>TOXICITY</td> <td>IRRITATION</td> </tr> </table> | TOXICITY | IRRITATION |
| TOXICITY | IRRITATION | | |

| | | |
|--|---|---|
| | Not Available | Not Available |
| naphtha, petroleum, hydrodesulfurised heavy | TOXICITY | IRRITATION |
| | Dermal (rabbit) LD50: >1900 mg/kg ^[1] | Not Available |
| | Dermal (rabbit) LD50: >1900 mg/kg ^[1] | |
| | Dermal (rabbit) LD50: >1900 mg/kg ^[1] | |
| | Dermal (rabbit) LD50: >1900 mg/kg ^[1] | |
| | Dermal (rabbit) LD50: >3000 mg/kg ^[2] | |
| | dermal (rat) LD50: 28000 mg/kg ^[2] | |
| | Inhalation (rat) LC50: >1400 ppm/8hr ^[2] | |
| | Inhalation (rat) LC50: 3400 ppm/4hr ^[2] | |
| | Inhalation (rat) LC50: 61 mg/L/4hr ^[2] | |
| | Oral (rat) LD50: >19650 mg/kg ^[2] | |
| | Oral (rat) LD50: >4300 mg/kg ^[2] | |
| | Oral (rat) LD50: >4500 mg/kg ^[1] | |
| | Oral (rat) LD50: >4500 mg/kg ^[1] | |
| | Oral (rat) LD50: >4500 mg/kg ^[1] | |
| | Oral (rat) LD50: >5000 mg/kg ^[2] | |
| | xylene | TOXICITY |
| Dermal (rabbit) LD50: >1700 mg/kg ^[2] | | Eye (human): 200 ppm irritant |
| Inhalation (rat) LC50: 5000 ppm/4hr ^[2] | | Eye (rabbit): 5 mg/24h SEVERE |
| Oral (rat) LD50: 4300 mg/kg ^[2] | | Eye (rabbit): 87 mg mild Skin (rabbit):500 mg/24h moderate |
| N-methyl-2-pyrrolidone | TOXICITY | IRRITATION |
| | dermal (rat) LD50: >5000 mg/kg ^[1] | Eye (rabbit): 100 mg - moderate |
| | Inhalation (rat) LC50: 8300 ppm/4hr ^[2] | |
| | Oral (rat) LD50: 3914 mg/kg ^[2] | |

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

| | | | |
|-----------------------------------|---|--------------------------|---|
| Acute Toxicity | ☒ | Carcinogenicity | ☒ |
| Skin Irritation/Corrosion | ☒ | Reproductivity | ☒ |
| Serious Eye Damage/Irritation | ☒ | STOT - Single Exposure | ☒ |
| Respiratory or Skin sensitisation | ☒ | STOT - Repeated Exposure | ✓ |
| Mutagenicity | ☒ | Aspiration Hazard | ✓ |

Legend: ✗ – Data available but does not fill the criteria for classification
 ✓ – Data required to make classification available
 ☒ – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

| Ingredient | Endpoint | Test Duration (hr) | Species | Value | Source |
|---|----------|--------------------|-------------------------------|-----------|--------|
| naphtha, petroleum, hydrodesulfurised heavy | EC50 | 72 | Algae or other aquatic plants | =13mg/L | 1 |
| naphtha, petroleum, hydrodesulfurised heavy | EC50 | 72 | Algae or other aquatic plants | =3000mg/L | 1 |
| naphtha, petroleum, hydrodesulfurised heavy | NOEC | 72 | Algae or other aquatic plants | =0.1mg/L | 1 |
| naphtha, petroleum, hydrodesulfurised heavy | EC50 | 48 | Crustacea | >100mg/L | 1 |

Continued...

| | | | | | |
|---|------|-----|-------------------------------|-------------|---|
| naphtha, petroleum, hydrodesulfurised heavy | EC50 | 96 | Algae or other aquatic plants | =450mg/L | 1 |
| naphtha, petroleum, hydrodesulfurised heavy | EC50 | 72 | Algae or other aquatic plants | =6.5mg/L | 1 |
| naphtha, petroleum, hydrodesulfurised heavy | EC50 | 72 | Algae or other aquatic plants | =6.5mg/L | 1 |
| naphtha, petroleum, hydrodesulfurised heavy | NOEC | 72 | Algae or other aquatic plants | <0.1mg/L | 1 |
| naphtha, petroleum, hydrodesulfurised heavy | LC50 | 96 | Fish | 0.00746mg/L | 4 |
| naphtha, petroleum, hydrodesulfurised heavy | EC50 | 48 | Crustacea | 0.058mg/L | 4 |
| naphtha, petroleum, hydrodesulfurised heavy | BCF | 96 | Fish | 0.2mg/L | 4 |
| naphtha, petroleum, hydrodesulfurised heavy | EC20 | 168 | Crustacea | 0.11mg/L | 4 |
| naphtha, petroleum, hydrodesulfurised heavy | NOEC | 168 | Crustacea | <=0.05mg/L | 4 |
| naphtha, petroleum, hydrodesulfurised heavy | LC50 | 96 | Fish | 8.8mg/L | 4 |
| naphtha, petroleum, hydrodesulfurised heavy | EC50 | 48 | Crustacea | 3.7mg/L | 4 |
| naphtha, petroleum, hydrodesulfurised heavy | EC50 | 72 | Algae or other aquatic plants | =6.5mg/L | 1 |
| naphtha, petroleum, hydrodesulfurised heavy | EC50 | 72 | Algae or other aquatic plants | =4700mg/L | 1 |
| naphtha, petroleum, hydrodesulfurised heavy | NOEC | 72 | Algae or other aquatic plants | <0.1mg/L | 1 |
| naphtha, petroleum, hydrodesulfurised heavy | EC50 | 72 | Algae or other aquatic plants | =6.5mg/L | 1 |
| naphtha, petroleum, hydrodesulfurised heavy | EC50 | 72 | Algae or other aquatic plants | =6.5mg/L | 1 |
| naphtha, petroleum, hydrodesulfurised heavy | NOEC | 72 | Algae or other aquatic plants | <0.1mg/L | 1 |
| xylene | LC50 | 96 | Fish | 2.6mg/L | 2 |
| xylene | EC50 | 48 | Crustacea | >3.4mg/L | 2 |
| xylene | EC50 | 72 | Algae or other aquatic plants | 4.6mg/L | 2 |
| xylene | EC50 | 24 | Crustacea | 0.711mg/L | 4 |
| xylene | NOEC | 73 | Algae or other aquatic plants | 0.44mg/L | 2 |
| N-methyl-2-pyrrolidone | LC50 | 96 | Fish | 464mg/L | 1 |
| N-methyl-2-pyrrolidone | EC50 | 48 | Crustacea | ca.4897mg/L | 1 |
| N-methyl-2-pyrrolidone | EC50 | 72 | Algae or other aquatic plants | >500mg/L | 1 |
| N-methyl-2-pyrrolidone | EC50 | 384 | Crustacea | 133.481mg/L | 3 |
| N-methyl-2-pyrrolidone | NOEC | 504 | Crustacea | 12.5mg/L | 2 |

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|------------------------|-----------------------------|-----------------------------|
| xylene | HIGH (Half-life = 360 days) | LOW (Half-life = 1.83 days) |
| N-methyl-2-pyrrolidone | LOW | LOW |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|------------------------|--------------------|
| xylene | MEDIUM (BCF = 740) |
| N-methyl-2-pyrrolidone | LOW (BCF = 0.16) |

Mobility in soil

| Ingredient | Mobility |
|------------------------|-------------------|
| N-methyl-2-pyrrolidone | LOW (KOC = 20.94) |

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

| | |
|------------------------------|---|
| Product / Packaging disposal | <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> ▶ Reduction ▶ Reuse ▶ Recycling ▶ Disposal (if all else fails) <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means.</p> <ul style="list-style-type: none"> ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ It may be necessary to collect all wash water for treatment before disposal. ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▶ Where in doubt contact the responsible authority. ▶ Recycle wherever possible. ▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. ▶ Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material). ▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed. |
|------------------------------|---|

SECTION 14 TRANSPORT INFORMATION

Labels Required

| | |
|------------------|---|
| |  |
| Marine Pollutant | NO |
| HAZCHEM | •3Y |

Land transport (ADG)

| | | | | | |
|------------------------------|--|--------------------|-------------|------------------|----------------|
| UN number | 1263 | | | | |
| UN proper shipping name | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) | | | | |
| Transport hazard class(es) | <table border="1"> <tr> <td>Class</td> <td>3</td> </tr> <tr> <td>Subrisk</td> <td>Not Applicable</td> </tr> </table> | Class | 3 | Subrisk | Not Applicable |
| Class | 3 | | | | |
| Subrisk | Not Applicable | | | | |
| Packing group | III | | | | |
| Environmental hazard | Not Applicable | | | | |
| Special precautions for user | <table border="1"> <tr> <td>Special provisions</td> <td>163 223 367</td> </tr> <tr> <td>Limited quantity</td> <td>5 L</td> </tr> </table> | Special provisions | 163 223 367 | Limited quantity | 5 L |
| Special provisions | 163 223 367 | | | | |
| Limited quantity | 5 L | | | | |

Air transport (ICAO-IATA / DGR)

| | | | | | | | | | | | | | | | |
|---|---|--------------------|-------------|---------------------------------|----------------|-------------------------------|-------|--|-----|--|------|---|------|--|------|
| UN number | 1263 | | | | | | | | | | | | | | |
| UN proper shipping name | Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base); Paint related material (including paint thinning or reducing compounds) | | | | | | | | | | | | | | |
| Transport hazard class(es) | <table border="1"> <tr> <td>ICAO/IATA Class</td> <td>3</td> </tr> <tr> <td>ICAO / IATA Subrisk</td> <td>Not Applicable</td> </tr> <tr> <td>ERG Code</td> <td>3L</td> </tr> </table> | ICAO/IATA Class | 3 | ICAO / IATA Subrisk | Not Applicable | ERG Code | 3L | | | | | | | | |
| ICAO/IATA Class | 3 | | | | | | | | | | | | | | |
| ICAO / IATA Subrisk | Not Applicable | | | | | | | | | | | | | | |
| ERG Code | 3L | | | | | | | | | | | | | | |
| Packing group | III | | | | | | | | | | | | | | |
| Environmental hazard | Not Applicable | | | | | | | | | | | | | | |
| Special precautions for user | <table border="1"> <tr> <td>Special provisions</td> <td>A3 A72 A192</td> </tr> <tr> <td>Cargo Only Packing Instructions</td> <td>366</td> </tr> <tr> <td>Cargo Only Maximum Qty / Pack</td> <td>220 L</td> </tr> <tr> <td>Passenger and Cargo Packing Instructions</td> <td>355</td> </tr> <tr> <td>Passenger and Cargo Maximum Qty / Pack</td> <td>60 L</td> </tr> <tr> <td>Passenger and Cargo Limited Quantity Packing Instructions</td> <td>Y344</td> </tr> <tr> <td>Passenger and Cargo Limited Maximum Qty / Pack</td> <td>10 L</td> </tr> </table> | Special provisions | A3 A72 A192 | Cargo Only Packing Instructions | 366 | Cargo Only Maximum Qty / Pack | 220 L | Passenger and Cargo Packing Instructions | 355 | Passenger and Cargo Maximum Qty / Pack | 60 L | Passenger and Cargo Limited Quantity Packing Instructions | Y344 | Passenger and Cargo Limited Maximum Qty / Pack | 10 L |
| Special provisions | A3 A72 A192 | | | | | | | | | | | | | | |
| Cargo Only Packing Instructions | 366 | | | | | | | | | | | | | | |
| Cargo Only Maximum Qty / Pack | 220 L | | | | | | | | | | | | | | |
| Passenger and Cargo Packing Instructions | 355 | | | | | | | | | | | | | | |
| Passenger and Cargo Maximum Qty / Pack | 60 L | | | | | | | | | | | | | | |
| Passenger and Cargo Limited Quantity Packing Instructions | Y344 | | | | | | | | | | | | | | |
| Passenger and Cargo Limited Maximum Qty / Pack | 10 L | | | | | | | | | | | | | | |

Sea transport (IMDG-Code / GGVSee)

| | | |
|-------------------------------------|--|-----------------|
| UN number | 1263 | |
| UN proper shipping name | PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) | |
| Transport hazard class(es) | IMDG Class | 3 |
| | IMDG Subrisk | Not Applicable |
| Packing group | III | |
| Environmental hazard | Not Applicable | |
| Special precautions for user | EMS Number | F-E, S-E |
| | Special provisions | 163 223 367 955 |
| | Limited Quantities | 5 L |

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION**Safety, health and environmental regulations / legislation specific for the substance or mixture****NAPHTHA, PETROLEUM, HYDRODESULFURISED HEAVY(64742-82-1.) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft

XYLENE(1330-20-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

N-METHYL-2-PYRROLIDONE(872-50-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

| National Inventory | Status |
|-------------------------------|--|
| Australia - AICS | Y |
| Canada - DSL | Y |
| China - IECSC | Y |
| Europe - EINEC / ELINCS / NLP | Y |
| Japan - ENCS | Y |
| Korea - KECI | Y |
| New Zealand - NZIoC | Y |
| Philippines - PICCS | Y |
| USA - TSCA | Y |
| Legend: | Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

SECTION 16 OTHER INFORMATION**Other information****Ingredients with multiple cas numbers**

| Name | CAS No |
|---|---|
| naphtha, petroleum, hydrodesulfurised heavy | 64742-82-1., 64741-92-0., 8052-41-3., 1030262-12-4., 8032-32-4., 8030-30-6., 64742-88-7., 64742-89-8., 8002-05-9., 61789-95-5., 64742-48-9., 101795-02-2., 8031-06-9., 8030-31-7., 50813-73-5., 54847-97-1., 121448-83-7., 8031-38-7., 8031-39-8. |
| N-methyl-2-pyrrolidone | 872-50-4, 26138-58-9 |

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average

Continued...

PC—STEL: Permissible Concentration-Short Term Exposure Limit
IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit
IDLH: Immediately Dangerous to Life or Health Concentrations
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index