

BONA RETARDER

Bona Retarder is an additive that improves the levelling and prolongs the open time of Bona water-based finishes, both primers and top coats. It is designed to be used when low humidity and / or high temperatures are encountered. Using Bona Retarder reduces the risk of the Bona primer / finish drying too quickly or applicator marks being evident in the dried coat. Retarder can also be added to Bona Sportive Paint to give lower viscosity and better levelling.

- Facilitates application in dry and / or warm conditions
- Prolongs the open time
- Minimizes the risk of overlapping and discolouration

Technical data

Addition rate: Primer / Finish – Maximum 4%

Sportive Paint - Maximum 10%

Safety: Unclassified Flash point: Non-flammable

Shelf life: At least 2 years, from the date of production, in

unopened original container

Storage / transport: The temperature must not fall below +5°C or exceed

+25°C during storage and transport

Disposal: Wastes and emptied containers should be handles in

accordance with local regulations

Pack size: 200 ml

Preparation

Bona waterborne Primer / Finish

Add **Bona Retarder** to the Primer / finish in accordance with the measurements on the bottle and label. Determine the amount of finish required and add the Bona Retarder; maximum 4% of the finish quantity. Shake thoroughly.

Apply the mixed product as normal according to the primer / finish application instructions on the label / technical datasheet.

Bona Sportive Paint

Add up to 10% Bona Retarder to the paint. Stir thoroughly and apply the paint as normal according to the application instructions on the label / technical datasheet.

Important notes

The above information is provided in good faith and to the best of our current knowledge but makes no claim to be complete. The User is responsible for establishing that the product and recommendations herein are fit for the designated purpose, floor type and present situation before use. Bona can only guarantee the delivered product. A professional and thereby successful application of the product is beyond our control. If in doubt, make a preliminary test. The User is required to read and understand all information contained on package labels and safety data sheets before using this product.



Phone 1300 882 806