

# TECHNICAL INFORMATION

## WS 2K Contact



Water-based adhesion promoter for refinishing factory finished wood and cork floors without intermediate sanding.

- No sanding necessary – no dust
- The safest way to recoat textured, hand scraped and distressed surfaces
- Very high coverage

### Recommended use:

Suitable for high traffic commercial areas. For use over wood and cork flooring with factory applied UV cured finishes where additional coats of protection or a sheen change is required. Can also be used to correct light surface scratching to existing floors.

## Technical Data

### Art.-no.

11520

### Item-#:

LO-FI-008



1 qt.



4



360

### Storage and transportation

Shelf life: 12 months in unopened containers. Store and transport between 40°F to 75°F (5°C to 25°C). KEEP FROM FREEZING.

### US Regulatory VOC

< 240 g/l

## Information for Use

- For professional Use only!
- BEFORE USING, READ AND UNDERSTAND ALL LABEL INSTRUCTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our Loba-Wakol Technical Service at 1-800.230.6456.
- Recommended conditions are 55°F-80°F/40-75%rH.
- Do not apply at temperatures below 55°F (12°C). Make sure material is at room temperature. Always maintain adequate ventilation during all phases of the coating and drying process.
- ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE AND DESIRED RESULTS.
- Shake base well and add the complete unit of hardener to the base container.
- If partial quantities are needed, mix at a ratio of 2 parts base : 1 hardener by weight and thoroughly mix by shaking.
- POT LIFE: 2 hours.
- Do not thin. Do not add water.
- Apply evenly at the recommended coverage rate. Avoid streaks, puddles and lap marks.

23/07/2021



# TECHNICAL INFORMATION

## WS 2K Contact



### Information for Use

---

#### Application Tool

Foamed back TrimPad applicator

#### Coverage

500-600 square feet per quart.

#### Drying time

- 2 hours minimum.
- Must be coated within 24 hours.
- Surface of LOBA 2K Contact should be dry to the touch and have no "tackiness". Heavy application or high humidity will increase dry time. Application of finish too early can create visible defects in the finish.

#### Recommended Procedure for wood floors:

##### The C4 System

###### C1: Certify

Always test finish prior to application. Follow instructions as stated below in section C2-C4. Test adhesion after 5 days.

###### C2: Clean

Clean floor with LOBA Hardwood Floor Cleaner. For heavily soiled floors clean with LOBA Remover according to Technical Information.

###### C3: Contact

When floor is thoroughly clean and dry apply WS 2K Contact. Allow to dry completely.

###### C4: Coat

Apply one coat of WS 2K Supra or 2K Supra<sup>A.T.</sup>. According to Technical Information. Glossy finishes are not recommended.

#### Compatibility

When this product is used in combination with other LOBA products the Technical Information of these products must be followed.

23/07/2021



# TECHNICAL INFORMATION

## WS 2K Contact



### General guidelines

**Cleaning of tools:** Clean tools and equipment with water.

**Cure Time:** The stated drying and cure times are based on ideal conditions (68°F, 50% RH) at the recommended application rates. Insufficient ventilation, high humidity, lower temperatures, increased coat thickness can prolong the curing process considerably. Do not cover floors, replace carpets or rugs, or clean floors with a damp mop/cloth before the final curing has been reached.

**Safety Precautions:** Even when working with low or zero-emission products the usual safety measures must be taken. Keep away from children. Do not eat, drink or smoke in working areas. Wear suitable safety gloves. Clean left-overs off of hands. Change soiled clothes.

**First Aid:** If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If breathing is difficult or other respiratory complaints, remove to fresh air and get medical attention. In case of eye contact, immediately flush eyes for several minutes under running water. Generally, this product does not cause skin irritation. Call a physician if irritation occurs.

**Special Information** The information in this document and any other information or advice we provide is intended for our customers only, and all information and advice is subject to the terms and limitations in Loba-Wakol's General Terms and Conditions, including without limit its limited warranty ("Terms"). The Terms are not expanded, changed, or waived by the information in this document or by any information or advice given by Loba-Wakol. Loba-Wakol has no relationship or obligation to anyone other than the customer that originally purchases the product from Loba-Wakol. The information in this document and any other information or advice we provide is the result of our prior experience and our knowledge of our products. Due to the wide variety of application possibilities and processing conditions, it is the customer's responsibility to test our product for suitability for its intended purpose. When in doubt, call our Technical Service for support. Technical Information is also available by visiting our website [www.loba-wakol.com](http://www.loba-wakol.com). You must read and understand, and have your professional installer read and understand, all information contained in our Terms and in our published specifications, technical data sheets, written directions for installation, use and maintenance, and labels on the product. If you have any questions during application or use, immediately stop the application and use and contact our Technical Service. For information about other products offered by Loba-Wakol, please check the technical information concerning those products.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.

23/07/2021

