
Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.08.2021

Version number 4 (replaces version 3)

Revision: 19.08.2021



бB

Printing date 19.08.2021

Version number 4 (replaces version 3)

Revision: 19.08.2021

(Contd. of page 1)

Product name LOBADUR PrimaSeal Plus

· vPvB: Not applicable.

- **SECTION 3: Composition/information on ingredients**
- · 3.2 Mixtures

• Description: Mixture of the substances listed below with harmless additions.

· Dangerous components:		
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43-xxxx	ethanol	50-100%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; () Eye Irrit. 2, H319; STOT SE 3, H336	≥10-<20%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate 🚸 Flam. Liq. 3, H226; 아 STOT SE 3, H336, EUH066	5-10%

• Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· After inhalation Supply fresh air; consult doctor in case of symptoms.

· After skin contact The product is not skin irritating.

• After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.

• *After swallowing* In case of persistent symptoms consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

• 5.3 Advice for firefighters

• Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Prevent material from reaching sewage system, holes and cellars.

Inform respective authorities in case product reaches water or sewage system.

Dilute with much water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.08.2021

Version number 4 (replaces version 3)

Revision: 19.08.2021

Product name LOBADUR PrimaSeal Plus

· 6.4 Reference to other sections

See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Keep containers tightly sealed.
Store in cool, dry conditions in well sealed containers.
Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

- Requirements to be met by storerooms and containers: Store in cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed. Store in cool, dry conditions in well sealed containers.
- Storage class 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

• *Additional information:* The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

• Appropriate engineering controls No further data; see item 7.

· Individual protection measures, such as personal protective equipment

- · General protective and hygienic measures Wash hands during breaks and at the end of the work.
- **Breathing equipment:** Not required.

· Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.4 mm

(Contd. on page 4)

(Contd. of page 2)

GB

Printing date 19.08.2021

*

Version number 4 (replaces version 3)

Revision: 19.08.2021

Product name LOBADUR PrimaSeal Plus

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

Value for the permeation: Level ≤ 6

• Eye/face protection Tightly sealed safety glasses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical p General Information	
Physical state	Fluid
Colour:	Colourless
Smell:	Solvent-like
Odour threshold:	Not determined.
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and boiling	
range	>78 °C
Flammability	Not applicable.
Lower:	2 Vol %
Upper:	19 Vol %
Flash point:	10 °C
Self-inflammability:	Product is not selfigniting.
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	1107 wowinitian.
Kinematic viscosity at 20 °C	62-68 s (ISO 3 mm)
dynamic:	Not determined.
Solubility	1101 aciel minica.
Water:	Fully miscible
Partition coefficient n-octanol/water (log value)	Not determined.
Steam pressure:	Not determined.
-	Not determined.
Density and/or relative density	0.921 c/cm^3
Density at 20 °C	0.821 g/cm^3
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health an	nd
environment, and on safety.	
Ignition temperature:	370 °C
Explosive properties:	Product is not explosive. However, formation of
	explosive air/steam mixtures is possible.
Change in condition	
Evaporation rate	Not determined.
•	es
Information with regard to physical hazard class	
Information with regard to physical hazard class Explosives	Void
Information with regard to physical hazard class Explosives Flammable gases	Void Void
Information with regard to physical hazard class Explosives Flammable gases Aerosols	Void Void Void
Information with regard to physical hazard class Explosives Flammable gases Aerosols Oxidising gases	Void Void Void Void
Information with regard to physical hazard class Explosives Flammable gases Aerosols Oxidising gases Gases under pressure	Void Void Void Void Void
Information with regard to physical hazard class Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids	Void Void Void Void Void Highly flammable liquid and vapour.
Information with regard to physical hazard class Explosives Flammable gases Aerosols Oxidising gases Gases under pressure	Void Void Void Void Void

(Contd. of page 3)

GB

Printing date 19.08.2021

Version number 4 (replaces version 3)

Revision: 19.08.2021

Product name LOBADUR PrimaSeal Plus

		(Contd. of page 4)
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamma	ıble	
gases in contact with water	Void	
• Oxidising liquids	Void	
• Oxidising solids	Void	
· Organic peroxides	Void	
• Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

· LD/LC50	· LD/LC50 values that are relevant for classification:		
64-17-5 eti	64-17-5 ethanol		
Oral	LD50	7,060 mg/kg (rat)	
Inhalative	LC50/4 h	20,000 mg/l (rat)	
67-63-0 pr	67-63-0 propan-2-ol		
Oral	LD50	5,840 mg/kg (rat)	
Dermal	LD50	13,400 mg/kg (rab)	
Inhalative	LC50/4 h	30 mg/l (rat)	
123-86-4 n	123-86-4 n-butyl acetate		
Oral	LD50	14,000 mg/kg (rat)	
Inhalative	LC50/4 h	>21 mg/l (rat)	
	Serious eye damage/irritation Causes serious eye irritation. 11.2 Information on other hazards		
• Endocrine	Endocrine disrupting properties		

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.08.2021

Version number 4 (replaces version 3)

Revision: 19.08.2021

Product name LOBADUR PrimaSeal Plus

· 12.6 Endocrine disrupting properties

- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.

· Uncleaned packagings:

- *Recommendation: Disposal must be made according to official regulations.*
- Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR	1263 PAINT (vapour pressure at 50°C not more that
	110 kPa)
· IMDG, IATA	PAINT
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDĞ, IATA	II
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Kemler Number:	33
• EMS Number:	<i>F-E,<u>S-E</u></i>
· Stowage Category	В
· 14.7 Maritime transport in bulk according	g to IMO
instruments	Not applicable.
	(Contd. on page 7

(Contd. of page 5)

Version number 4 (replaces version 3)

Revision: 19.08.2021

Product name LOBADUR PrimaSeal Plus

Printing date 19.08.2021

	(Contd. of page 6
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
• Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT (VAPOUR PRESSURE AT 50°C NOT
-	MORE THAN 110 KPA), 3, II

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations

· Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Alteration in the context will be marked with a cross (*).

· Relevant phrases

Highly flammable liquid and vapour. H225

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing data specification sheet: Productmanagement.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 8)

Printing date 19.08.2021

Version number 4 (replaces version 3)

Revision: 19.08.2021

Product name LOBADUR PrimaSeal Plus

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 • * **Data compared to the previous version altered.** (Contd. of page 7)

GB