

**LOBADUR** 

# 2K InvisibleProtect

2K waterbased surface protection

## Inspired by natural wood – invisible protection

If you walk on it barefoot, you'll just love it!

High-quality and innovative raw materials are the key to making LOBADUR 2K InvisibleProtect a truly unique surface coating. The wood looks and feels untreated and offers you all the protection of a finished floor. High durability and easy cleaning combine to make LOBADUR 2K InvisibleProtect the perfect surface treatment for all lovers of natural wood.



## Why end users are convinced of 2K InvisibleProtect A.T.:

- Invisible protection – the look, feel and color of the wood remain as if it was untreated
- Long-lasting natural beauty – high resistance to mechanical wear and household chemicals
- Simple and convenient cleaning
- Very low emission
- Time saving – light use after 24 hours, fully resistant after only 5 days

## Why contractors are enthusiastic about 2K InvisibleProtect A.T.:

- Excellent application performance – safe and easy to use
- Full build-up in two layers, no primer needed
- Low VOC value, very low emission, EMICODE® EC1 PLUS
- Meets the OSHA requirements for walking surfaces of 0.5 (ASTM D2047-04)

## Special feature

LOBADUR 2K InvisibleProtect A.T. is a unique surface treatment. In addition to being invisible, it also feels incredibly like untreated wood. The latest generation of raw materials guarantees that the floor will be long-lasting and will not be polished up even under heavy wear.

## Range of use

Suitable for wood and cork floors. For heavy traffic residential areas and commercial use.

## Application

- Sand and remove dust from the surface properly
- First coat 2K InvisibleProtect with LOBATool roller Universal 100
- Intermediate sanding after 4-6 hours with 180 grit or maroon pad to remove grain raise
- Second coat 2K InvisibleProtect A.T with LOBATool roller Universal 100
- Optionally a third coat of 2K InvisibleProtect A.T. after another intermediate sanding
- Coverage: 400-500 square feet per gallon



LO-FI-238

Available in 1 Gal.

US Regulatory  
VOC < 140g/l



LOBA is always at your side and ensures your success with both advice and action. Our experienced experts are happy to support you individually with your projects. Our competent technical service team is at your disposal quickly, if you need hands-on assistance on site. You can always rely on us!

Do you have any questions? Do not hesitate to contact us:

**Please consider the detailed technical information, application advices and set-up recommendations.**

Technical Information



**Loba Wakol LLC**

2401 Whitehall Park Dr, Suite 950 | Charlotte, NC 28273 | Phone: (704) 527-5919 | E-Mail: info@loba-wakol.com | www.loba-wakol.com