

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2021

Reviewed on 02/01/2021

1 Identification

- **Product identifier**
- **Trade name:** LOBADUR 2K Supra A.T.
- **Article number:** 11465-250
- **Application of the substance / the mixture**
Dispersion paint/ Latex paint
Multi-pack product
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Loba Wakol LLC
2732 Hwy 74 West
Wadesboro, NC 28170
Phone: (800) 230-6456
Email: info@loba-wakol.com
- **Emergency telephone number:**
For Emergency Assistance Involving Chemicals - Call INFOTRAC US. 800-535-5053
International: INFOTRAC, Tel + 1 352 323 3500
Info you need when you call: Product Name or Manufacturer Name

2 Hazard(s) identification

- **Classification of the substance or mixture**
The product is not classified, according to the Globally Harmonized System (GHS).

- **Label elements**
- **GHS label elements** Void
- **Hazard pictograms** Void
- **Signal word** Void
- **Hazard statements** Void
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 0
Fire = 0
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 0
Fire = 0
Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2021

Reviewed on 02/01/2021

Trade name: **LOBADUR 2K Supra A.T.**

(Contd. of page 1)

· Dangerous components:

CAS: 34590-94-8	Dipropylene glycol monomethyl ether	2.5-5%
EINECS: 252-104-2	Flam. Liq. 4, H227	
CAS: 111-76-2	2-butoxyethanol	<2.5%
EINECS: 203-905-0	⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Flam. Liq. 4, H227	

· Additional information: For the wording of the listed hazard phrases refer to section 16.**4 First-aid measures**

- **Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**
No dangerous substances are released.
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

9009-54-5	polyurethane without free isocyanate	12 mg/m ³
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
111-76-2	2-butoxyethanol	60 ppm
121-44-8	triethylamine	1 ppm

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2021

Reviewed on 02/01/2021

Trade name: **LOBADUR 2K Supra A.T.**

(Contd. of page 2)

78-10-4	tetraethyl orthosilicate	25 ppm
67-64-1	acetone	200 ppm
57-55-6	Propylene glycol	30 mg/m ³
63148-62-9	Polydimethylsiloxane	65 mg/m ³
67-63-0	propan-2-ol	400 ppm
556-67-2	octamethylcyclotetrasiloxane	30 ppm

· **PAC-2:**

9009-54-5	polyurethane without free isocyanate	130 mg/m ³
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
111-76-2	2-butoxyethanol	120 ppm
121-44-8	triethylamine	170 ppm
78-10-4	tetraethyl orthosilicate	100 ppm
67-64-1	acetone	3200* ppm
57-55-6	Propylene glycol	1,300 mg/m ³
63148-62-9	Polydimethylsiloxane	720 mg/m ³
67-63-0	propan-2-ol	2000* ppm
556-67-2	octamethylcyclotetrasiloxane	68 ppm

· **PAC-3:**

9009-54-5	polyurethane without free isocyanate	790 mg/m ³
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
111-76-2	2-butoxyethanol	700 ppm
121-44-8	triethylamine	1,000 ppm
78-10-4	tetraethyl orthosilicate	300 ppm
67-64-1	acetone	5700* ppm
57-55-6	Propylene glycol	7,900 mg/m ³
63148-62-9	Polydimethylsiloxane	4,300 mg/m ³
67-63-0	propan-2-ol	12000** ppm
556-67-2	octamethylcyclotetrasiloxane	130 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Storage class:** 12
- **Specific end use(s)** No further relevant information available.

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2021

Reviewed on 02/01/2021

Trade name: **LOBADUR 2K Supra A.T.**

(Contd. of page 3)

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

34590-94-8 Dipropylene glycol monomethyl ether

PEL	Long-term value: 600 mg/m ³ , 100 ppm Skin
REL	Short-term value: 900 mg/m ³ , 150 ppm Long-term value: 600 mg/m ³ , 100 ppm Skin
TLV	Short-term value: NIC-606 (909) mg/m ³ , NIC-100 (150) ppm Long-term value: NIC-303 (606) mg/m ³ , NIC-50 (100) ppm (Skin)

111-76-2 2-butoxyethanol

PEL	Long-term value: 240 mg/m ³ , 50 ppm Skin
REL	Long-term value: 24 mg/m ³ , 5 ppm Skin
TLV	Long-term value: 97 mg/m ³ , 20 ppm BEI

· **Ingredients with biological limit values:**

111-76-2 2-butoxyethanol

BEI	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

· **Breathing equipment:** Not required.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.4 mm

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

Value for the permeation: Level ≤ 6

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2021

Reviewed on 02/01/2021

Trade name: **LOBADUR 2K Supra A.T.**

(Contd. of page 4)

· **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**· **Form:** Fluid· **Color:** According to product specification· **Odor:** Recognizable· **Odor threshold:** Not determined.· **pH-value:** Not determined.· **Change in condition**· **Melting point/Melting range:** Undetermined.· **Boiling point/Boiling range:** 100 °C (212 °F)· **Flash point:** Not applicable.· **Flammability (solid, gaseous):** Not applicable.· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** Product does not present an explosion hazard.· **Lower:** Not determined.· **Upper:** Not determined.· **Vapor pressure:** Not determined.· **Density at 20 °C (68 °F):** 1.05 g/cm³ (8.76225 lbs/gal)· **Relative density** Not determined.· **Vapor density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with**· **Water:** Not miscible or difficult to mix.· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**· **Dynamic:** Not determined.· **Kinematic at 20 °C (68 °F):** 17 s (ISO 4 mm)· **Other information** No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.· **Chemical stability**· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.· **Possibility of hazardous reactions** No dangerous reactions known.· **Conditions to avoid** No further relevant information available.· **Incompatible materials:** No further relevant information available.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2021

Reviewed on 02/01/2021

Trade name: **LOBADUR 2K Supra A.T.**

(Contd. of page 5)

· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:****34590-94-8 Dipropylene glycol monomethyl ether**

Oral LD50 5,135 mg/kg (rat)

Dermal LD50 9,500 mg/kg (rat)

111-76-2 2-butoxyethanol

Oral LD50 1,480 mg/kg (rat)

Dermal LD50 400 mg/kg (rab)

Inhalative LC50/4 h 450 mg/l (rat)

· **Primary irritant effect:**· **on the skin:** No irritant effect.· **on the eye:** No irritating effect.· **Sensitization:** No sensitizing effects known.· **Additional toxicological information:**

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

9009-54-5 polyurethane without free isocyanate

3

111-76-2 2-butoxyethanol

3

67-63-0 propan-2-ol

3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.· **Behavior in environmental systems:**· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.· **Additional ecological information:**· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2021

Reviewed on 02/01/2021

Trade name: **LOBADUR 2K Supra A.T.**

(Contd. of page 6)

- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
After prior treatment product has to be landfilled or incinerated adhering to the regulations pertaining to the disposal of especially hazardous waste.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|-----------------|
| · UN-Number | |
| · DOT, ADR, ADN, IMDG, IATA | not regulated |
| · UN proper shipping name | |
| · DOT, ADR, ADN, IMDG, IATA | not regulated |
| · Transport hazard class(es) | |
| · DOT, ADR, ADN, IMDG, IATA | |
| · Class | not regulated |
| · Packing group | |
| · DOT, ADR, IMDG, IATA | not regulated |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | not regulated |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **TSCA (Toxic Substances Control Act):** All components are on the TSCA inventory

· **Hazardous Air Pollutants**

121-44-8 triethylamine

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2021

Reviewed on 02/01/2021

Trade name: **LOBADUR 2K Supra A.T.**

(Contd. of page 7)

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **GHS label elements** Void

· **Hazard pictograms** Void

· **Signal word** Void

· **Hazard statements** Void

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H227 Combustible liquid.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

· **Department issuing SDS:** Productmanagement.

· **Contact:**

· **Date of preparation / last revision** 02/08/2021 / 7

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

· *** Data compared to the previous version altered.**

US