



LOBADUR®

2K Supra

ADVANCED
TECHNOLOGY

Ceramic-reinforced waterbased 2-component polyurethane finish for wood floors

Super durable, Supra scratch-resistant – ready for full use after 12 hours!

The most scratch-resistant waterbased finish on the market – for long-lasting protection and a rich surface

Do you have high expectations? So do we! Choose 2K Supra A.T. with optimized formula and benefit from an extremely resistant and durable surface. Make use of the time advantage: the finished floor can be fully used after only 12 hours.

Optimized
Formula



LOBA – Your partner for surface finishing and care

Why end users choose 2K Supra A.T.:

- Long-lasting flooring thanks to optimized protection against scratches and high resistance
- Can be fully used after only 12 hours
- Very low emissions
- Increased slip resistance

Why contractors choose 2K Supra A.T.:

- Excellent flow and wetting properties due to an optimized formula
- Excellent scratch-resistance thanks to innovative ceramic reinforcement
- Excellent resistance against chemicals, friction and wear
- Can be fully used after 12 hours
- Very low emissions, EMICODE® EC1
- Coefficient of sliding friction > 0.5 according to DIN 18032 for sports flooring
- FIBA approved for international basketball floors: variant satin

Special feature

The ceramic-reinforced water-based polyurethane floor finish provides an extremely scratch-resistant surface and offers long-lasting protection.

Range of use

Perfect for demanding and high-traffic floors, such as in restaurants, shops, and sports halls. Suitable for wood flooring as well as cork, linoleum, and PVC coverings. Achieves the coefficient of sliding friction according to DIN 18032 for sports flooring. For extremely heavy use.

Application

- Sand floors and vacuum to a dust free state
- Apply approved Loba Sealer as specified in TI
- First coat of 2K Supra A.T. with the LOBAT00L Microfiber 100–120 roller
- Intermediate sanding after 4 hours with LOBASAND P180 perforated pad
- Second coat of 2K Supra A.T. with the LOBAT00L Microfiber 100–120 roller
- Coverage per application: 400-500 sqft/gal. with the LOBAT00L Microfiber 100-120 roller



Article no. 11465

Available in satin and semi-gloss (1 gallon)

GISCODE W3/DD+



LOBA is always at your side and ensures your success with both advice and action. Our experienced application specialists will advise you personally with your projects.

Our competent service team is quickly on hand if you need practical support directly on site. So you can be confident right from the start and know who you can rely on at all times.

Always refer to the Technical Data sheet for greater details.

Technical information



Loba Wakol LLC

2732 Hwy 74 West | Wadesboro, NC 28170 | Phone: (800)230-6456 | E-Mail: info@loba-wakol.com | www.loba-wakol.com