

TECHNICAL INFORMATION

PreTone VARIOUS COLORS



Water-based pigment stain for wooden floors. Color intensification under oxidizing oils.

- Allows an infinite amount of customization
- Intensifies light colors
- Reduces oil-specific amberizing
- Simple and safe application
- Solvent-free and odor-neutral
- Unlimited color combinations

Recommended use:

On sanded wood floors prior to the application of LOBASOL® HS 2K ImpactOil or LOBADUR® HS 2K IntensiveColor ^{A.T.}. LOBASOL® PreTone colors can be mixed at any ratio to achieve custom colors.

Technical Data

Art.-no.

10612



2,5 l



6



216

Solids

2.4 ±2%

pH

7.0

Contents

water, nonionic surfactants, dyes, pigments, preservatives

Storage and transportation

Shelf life: 24 months in unopened containers. Store and transport between 40°F to 80°F (5°C to 25°C). KEEP FROM FREEZING.



LO-FI-240
Black

LO-FI-241
Brown

LO-FI-267
Mocha

LO-FI-266
Steel

LO-FI-237
White

Color samples are not binding

13/12/2019



TECHNICAL INFORMATION

PreTone VARIOUS COLORS



Technical Data

Suitability list woodtypes:

North American/European Species

Maple (Canadian)	+
Maple (European)	+
Acacia / Yellow Locust	+
Acacia / Yellow Locust steamed	+
Birch	+
Pear tree	+
Beech steamed	+
Beech natural	+
White Oak	+
Alder	+
Ash	+
Spruce	+
Chestnut tree	+
Pine	+
Black cherry	+
Cherry (European)	+
Larch	+
Walnut (European)	+
Olive tree	+
Smoked oak	+
Red Oak	+
Elm	+

Further Species

Afromosia / Kokrodua	+
Arrurra Vermelho	+
Bamboo	+
basralocus wood	+
Opepe	+
Cabreuva	+
Coigue steamed	+
Cumaru / Almendrillo	+
Curupau	+
Curupay	+
Doussie / Afzelia	+
Ebony / Makassar	+
Eucalyptus / Jarrah	+
Eucalyptus / Spottet Gum	+
Guatambu	+
Hard Pine (new floors)	+
Rubberwood	+
Inciense Colorado	+
Ipe / Lapacho / Guaycan	+
Iroko / Kambala	+
Iron Wood	+
Jatoba / Brazilian Cherry	+
Kempas	+
Coconut	+
Kotibe / Mahogany	+

Mahogany	+
Mahogany Acajou	+
Massaranduba	+
Mecrusse	+
Moluccan Ironwood	+
Muhuhu	+
Mutenye	+
Camwood	+
rosewood	+
Partridge Wood	+
Piguia Marfin	+
Pitch Pine (old floors)	+
Purpleheart	+
Sucupira	+
Tasmanien Oak	+
Tuari	+
Teak	+
Tigerwood	+
Wenge	+
Yvyraro	+
Cypress	+

Other Surfaces

Multiplex	+
OSB Board	+
Chipboard	+

+ Without limitation applicable

◇ Application can cause problems. Consult LOBA prior to use.

- Use is not recommended



TECHNICAL INFORMATION

PreTone VARIOUS COLORS



Application

- For professional Use only!
- BEFORE USING, READ AND UNDERSTAND ALL LABEL INSTRUCTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our LOBA-WAKOL Technical Service at 1-800.230.6456.
- Sand and prepare floors according to NWFA instructions.
- **WARNING!** If you scrape, sand or remove old paint from wood floors, you may release lead dust. Follow local and/or federal requirements for lead removal. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.
- ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE AND DESIRED RESULTS.
- Shake material well before use.
- Do not thin. Do not add water.
- Do not apply at temperatures below 55°F. Make sure material is at room temperature. Always maintain adequate ventilation during all phases of the coating and drying process.
- Apply evenly at the recommended coverage rate. Avoid streaks and puddles and lap marks.

Application Tool

Trim-Pad Item 6041, Padco Applicator Item 6000, Pump sprayer with flat pattern nozzle, LOBATOOL Wischwiesel, Single disc machine, LOBASAND SpecialPad green

Coverage

app. 110 - 130 square feet per liter: 275 – 325sqft per container.
Depending on absorbency of the wood.
Determine the exact consumption by creating a sample area.

Drying time

- Drying over night.

13/12/2019



TECHNICAL INFORMATION

PreTone VARIOUS COLORS



Application

Wipe-application

- Apply PreTone liberally with a trim pad lengthwise along the grain.*
- Drying overnight.
- Break raised grains by using a buffing machine and a LOBASAND SpecialPad green and remove the sanding dust.

Spray-application

Spray application saves considerable time, especially on large areas, and offers an ergonomic way of working. Spray application should be done by 2 people because the material must be evened out immediately after spraying. Two or more sprayers should be used for areas larger than 1000 square feet. Fertiliser sprayers operated at constant pressure in conjunction with a special flat pattern nozzle with a 90° spray angle, e.g. GLORIA, have proven successful in the past.

- Prior to the application, mask directly adjacent areas (e.g. doors, skirtings etc.) with masking tape.
- Guide the spray nozzle at a constant distance and angle to the surface and apply approximately 110 - 130 square feet per liter PreTone evenly in successive widths. Even out the coverage with a LOBATOOL Wischwiesel immediately after a width has been applied.*
- Dry overnight.
- Break raised grains by using a buffing machine and a LOBASAND SpecialPad green and remove the sanding dust.

* Tip: When applying a second coat after two 2 minutes impact time, the colors are more intensive and homogeneous.

Impregnation

- Impregnate surface with LOBASOL® HS 2K ImpactOil or the HS 2K ImpactOil Color of your choice according to the products' technical information.
- Alternatively impregnate surface with LOBADUR® HS 2K IntensiveColor ^{A.T.} of your choice according to the technical information of the product. Roll on LOBADUR® finish according to technical information.

Compatibility

When this product is used in combination with other LOBA products the Technical Information of these products have to be followed. Always prepare test areas to determine suitability of other products than LOBA.



TECHNICAL INFORMATION

PreTone

VARIOUS COLORS



General guidelines

Cleaning of tools: Clean tools and equipment with water.

Cure Time: The stated drying and cure times are based on ideal conditions (68°F, 65% rH) at the recommended application rates. Recommended conditions are 50°F-80°F/40-75%rH). Insufficient ventilation, high humidity, lower temperatures, increased coat thickness can prolong the curing process considerably. Do not use safety covers on floor, do not replace carpets or rugs and also do not clean floors with a damp cloth before the final curing has been reached.

Safety Precautions: Even when working with low or zero-emission products the usual safety measures must be taken. Keep away from children. Do not eat, drink or smoke in working areas. Wear suitable safety gloves. Clean left-overs off of hands. Change soiled clothes.

First Aid: If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If breathing is difficult or other respiratory complaints, remove to fresh air and get medical attention. In case of eye contact, immediately flush eyes for several minutes under running water. Generally this product does not cause skin irritation. Call a physician if irritation occurs.

Special Information The information in this document and any other information or advice we provide is intended for our customers only, and all information and advice is subject to the terms and limitations in Loba-Wakol's General Terms and Conditions, including without limit its limited warranty ("Terms"). The Terms are not expanded, changed or waived by the information in this document or by any information or advice given by Loba-Wakol. Loba-Wakol has no relationship or obligation to anyone other than the customer that originally purchases the product from Loba-Wakol. The information in this document and any other information or advice we provide is the result of our prior experience and our knowledge of our products. Due to the wide variety of application possibilities and processing conditions, it is the customer's responsibility to test our product for suitability for its intended purpose. When in doubt, call our Technical Service for support. Technical Information is also available by visiting our website www.loba-wakol.com. You must read and understand, and have your professional installer read and understand, all information contained in our Terms and in our published specifications, technical data sheets, written directions for installation, use and maintenance, and labels on the product. If you have any questions during application or use, immediately stop the application and use and contact our Technical Service. For information about other products offered by Loba-Wakol, please check the technical information concerning those products.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.

13/12/2019

