

TECHNICAL INFORMATION

WS UV-Protect



Prevents the darkening of light colored wood under the influence of light. This primarily leads to problems when carpets or items of furniture are moved at a later date and the change in wood color becomes very noticeable. Shows good effects on many light colored wood types such as maple, birch, ash, spruce. Lightening of dark types of wood cannot be prevented by using this product.

- Maintains wood color for a long period
- Suitable for all LOBADUR® finishes

Recommended use:

Additive for all LOBA Water-based finishes protecting light colored wood species against yellowing from exposure to sunlight.

Technical Data

Art.-no.

11017

Item-#:

LO-FI-052



100 ml



15

Solids

20 ±2%

Viscosity DIN 4

10 ±2s

Storage and transportation

Shelf life: 12 months in unopened containers. Store and transport between 40°F to 80°F (5°C to 25°C). KEEP FROM FREEZING.

Application

- For professional Use only!
- BEFORE USING, READ AND UNDERSTAND ALL LABEL INSTRUCTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our LOBA-WAKOL Technical Service at 1-800.230.6456.
- Sand and prepare floors according to NWFA instructions.
- ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE AND DESIRED RESULTS.
- Shake material well before use.
- Do not thin. Do not add water.
- Do not apply at temperatures below 55°F. Make sure material is at room temperature. Always maintain adequate ventilation during all phases of the coating and drying process.
- Apply evenly at the recommended coverage rate. Avoid streaks and puddles and lap marks.

13/12/2019



TECHNICAL INFORMATION

WS UV-Protect



Application

Drying time

- WS UV-Protect does not alter the dry time of the desired finish.

Recommended Procedure for wood floors:

- Add WS UV-Protect only right before the application by shaking or stirring thoroughly.
- When using 2-component-systems (WS 2K Supra, 2K Supra ^{A.T.}) add WS UV-Protect only AFTER adding hardener to the mass!
- Perform application according to technical information of the finish.
- Finishes mixed with WS UV-Protect must be used within 24 hours, 2-component-systems within 2 hours.
- A longer pot life cannot be guaranteed.

Compatibility

When this product is used in combination with other LOBA products the Technical Information of these products have to be followed. Always prepare test areas to determine suitability of other products than LOBA.

13/12/2019



TECHNICAL INFORMATION

WS UV-Protect



General guidelines

Cleaning of tools: Clean tools and equipment with water.

Cure Time: The stated drying and cure times are based on ideal conditions (68°F, 65% rH) at the recommended application rates. Recommended conditions are 50°F-80°F/40-75%rH). Insufficient ventilation, high humidity, lower temperatures, increased coat thickness can prolong the curing process considerably. Do not use safety covers on floor, do not replace carpets or rugs and also do not clean floors with a damp cloth before the final curing has been reached.

Safety Precautions: Even when working with low or zero-emission products the usual safety measures must be taken. Keep away from children. Do not eat, drink or smoke in working areas. Wear suitable safety gloves. Clean left-overs off of hands. Change soiled clothes.

First Aid: If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If breathing is difficult or other respiratory complaints, remove to fresh air and get medical attention. In case of eye contact, immediately flush eyes for several minutes under running water. Generally this product does not cause skin irritation. Call a physician if irritation occurs.

Special Information The information in this document and any other information or advice we provide is intended for our customers only, and all information and advice is subject to the terms and limitations in Loba-Wakol's General Terms and Conditions, including without limit its limited warranty ("Terms"). The Terms are not expanded, changed or waived by the information in this document or by any information or advice given by Loba-Wakol. Loba-Wakol has no relationship or obligation to anyone other than the customer that originally purchases the product from Loba-Wakol. The information in this document and any other information or advice we provide is the result of our prior experience and our knowledge of our products. Due to the wide variety of application possibilities and processing conditions, it is the customer's responsibility to test our product for suitability for its intended purpose. When in doubt, call our Technical Service for support. Technical Information is also available by visiting our website www.loba-wakol.com. You must read and understand, and have your professional installer read and understand, all information contained in our Terms and in our published specifications, technical data sheets, written directions for installation, use and maintenance, and labels on the product. If you have any questions during application or use, immediately stop the application and use and contact our Technical Service. For information about other products offered by Loba-Wakol, please check the technical information concerning those products.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.

13/12/2019

