

PC300 - Portugal Cork WB Cork Floor Primer

TECHNICAL DATA SHEET

DESCRIPTION

PC300 is a water-based primer. It is low VOC, solvent free, and is especially designed for use with **Cork Contact Adhesive** and cork adhesive backed tiles.

METHOD OF APPLICATION

To obtain the best results, the materials to be bonded should be dry, clean, and free from dust, grit, oil, grease, and other contaminants that may affect final bond.

The minimum sub floor temperature prior to commencing preparation or primer application is 10°C. Apply an even coat of the water-based primer to surfaces by brush or roller. On porous surfaces a second application may be required, allow water to evaporate and primer to become dry prior to second application. Apply **Cork Contact Adhesive** on top of dried primer and on cork tile as instructed.

Allow Cork Contact Adhesive to become dry, then press both surfaces together, making sure sufficient pressure is applied to bring both surfaces into close contact.

CLEAN UP

Clean tools immediately after use with **warm soapy water**.

Dried primer may be softened using a **Nexus Adhesive Remover** or **Nexus 490 Solvent Cleaner**.

IMPORTANT: Do not use Nexus 490 Solvent Cleaner directly on finish floorcovering, as the solvent cleaner can potentially cause damage to the surface.

TYPICAL PROPERTIES

Appearance	milky liquid
Coverage	10 – 20 m ² per litre depending on sub-floor
Drying time	Approx. 30 minutes at 50% Relative Humidity and 21 °C.
Packaging	4 Litre
Shelf Life	12 months in sealed container at 20 °C

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Safety Data Sheet (SDS), available on request.

April 2023



Nexus Adhesives Pty Ltd

ABN 61 121 120 036

42 Healey Road
Dandenong South VIC 3175 Australia
Tel +61 3 9706 4022
Fax +61 3 9706 4122
www.nexusadhesives.com.au
info@nexusadhesives.com.au